



PRODUCT DATA SHEET

Size (cable)	A	B	C	D	L	M	M1
8	18	30	34	16	278	16x2 (LH)	26x2 (RH)
10	20	45	43	20	338	20x2 (LH)	33x2 (RH)
12	20	45	45	22	362	22x2 (LH)	34x2 (RH)
16	24	51	52.5	27	456	27x2 (LH)	42x2 (RH)
19	30	66	65	33	542	33x2 (LH)	52x2 (RH)
20	30	66	65	33	554	33x2 (LH)	52x2 (RH)
22	34	70	78	39	596	39x3 (LH)	62x2 (RH)
24	34	70	81	42	628	42x3 (LH)	65x3 (RH)
26	40	75	87	45	662	45x3 (LH)	70x3 (RH)
28	40	75	87	45	686	45x3 (LH)	70x3 (RH)
30	40	85	98	50	765	50x3 (LH)	78x3 (RH)
32	40	87	100	52	796	52x3 (LH)	80x3 (RH)
34	48	100	108	56	864	56x3 (LH)	84x3 (RH)
36	48	100	108	56	887	56x3 (LH)	84x3 (RH)
42	56	120	130	60	1,110	60x5.5 (LH)	100x6 (RH)

TECHNICAL DATA

Fork Material:	Cast AISI316, EN 1.4408
Terminal Material:	262 AR Bar AISI316, EN 1.4401
Yeild Strength:	262 MPa
Tensile strength:	515 MPa
Lock nut material:	AISI316, EN 1.4408
Pin material:	AISI316, EN 1.4401

100%
RECYCLABLE